













Quality timber windows sliding doors







TIMBER BIFOLD WINDOWS







Glazing in windows complies with AS 1288-1994 Wind Region A. Exposed Suburban. Purchaser to specify if window conditions vary from this.







All windows and doors are designed to 1000pa wind velocity and 150pa water rating.
ALL FRAMES ARE VIEWED FROM THE OUTSIDE.







STUD OPENING		785	935	1230	1230	1530	1830
Frame Size		765	915	1210	1210	1510	1810
1077	1057						
		IW22R1008	BW22R1009	BW22R1012	BW33R1012	BW44R1015	BW44R1018

STUD OPENING		1570	1570	1830	1830	2420	2420
Frame Size		1550	1550	1810	1810	2400	2400
1077	1057						
		BW44R1015	BW42L2R1015	BW44R1018	BW42L2R1018	BW44R1024	BW42L2R1024

STUD OPENING		785	935	1230	1230	1530	1830
Frame Size		765	915	1210	1210	1510	1810
1217	1197						
		IW22R1208	BW22R1209	BW22R1212	BW33R12152	BW33R1215	BW44R1218

STUD OPENING		1570	1570	1830	1830	2420	2420
Frame Size		1550	1550	1810	1810	2400	2400
1217	1197						
		BW44R1215	BW42L2R1215	BW44R1218	BW42L2R1218	BW44R1224	BW42L2R1224

STUD OPENING		785	935	1230	1230	1530	1830
Frame Size		765	915	1210	1210	1510	1810
1417	1397						
		IW22R1408	BW22R1409	BW22R1412	BW33R1412	BW33R1415	BW33R1418













STUD OPENING		1570	1570	1830	1830	2420	2420
Frame Size		1550	1550	1810	1810	2400	2400
1417	1397						
		BW44R1415	BW42L2R1415	BW44R1418	BW42L2R1418	BW44R1424	BW42L2R1424

Quality timber windows sliding doors

TIMBER BIFOLD WINDOWS

Glazing in windows complies with AS 1288-1994 Wind Region A. Exposed Suburban. Purchaser to specify if window conditions vary from this.

All windows and doors are designed to 1000pa wind velocity and 150pa water rating.
ALL FRAMES ARE VIEWED FROM THE OUTSIDE.

STUD OPENING		785	935	1230	1230	1530	1830		
Frame Size		765	915	1210	1210	1510	1810		
1517	1497								
		BW22R1508	BW22R1509	BW22R1512	BW33R1512	BW33R1515	BW44R1518		
		STUD OPENING		1570	1570	1830	1830	2420	2420
		Frame Size		1550	1550	1810	1810	2400	2400
		1517	1497						
				BW44R1515	BW42L2R1515	BW44R1518	BW42L2R1518	BW44R1524	BW42L2R1524